



## PETRYGO Q NEW COOLING SYSTEM FLUID

### GENERAL FEATURES:

A new formula of the most popular cooling fluid in Poland. The Petrygo Q New radiator fluid is manufactured using the highest quality ethylene glycol and a carefully selected set of additives to provide full protection of aluminium, cast-iron and mixed cooling systems. The fluid forms a very durable protective film in the system, providing corrosion and cavitation protection for the cooling system components for up to 100,000 km or 3 years. The fluid is frost resistant up to -35°. Can provide excellent protection against engine overheating. Petrygo Q NEW is neutral for the plastic elements of cooling systems. Optimal technology guarantees high stability of the fluid for long-term storage and use. The fluid is miscible with other fluids with similar parameters. \*\* vehicle manufacturers recommend the quality level for cooling liquids in order to provide the best possible protection of the cooling system. Does not contain toxic nitrites, silicates, amines, borates or phosphates.

- protects the cooling system against corrosion and cavitation
- safe for rubber and plastic elements
- guaranteed crystallization temperature -35°C
- protects the system against overheating
- prevents excessive deposits and limescale
- safe for the environment

### APPLICATION:

Universal fluid for all types of engine cooling systems – newer, mostly aluminum systems and older types of engines. Miscible with all available cooling fluids. The Petrygo Q New fluid can be stored for the period of 3 years from the date of production. The service life of the fluid in the cooling system is at least 3 years or 100,000 kilometres.

Ready-to-use fluid. Follow the manual supplied by the car manufacturer. Any loss is recommended to be replenished with the Petrygo Q or Petrygo Q NEW fluids. Shelf life: 3 years from the date on the packaging.

## STANDARDS, APPROVALS. SPECIFICATION:

Compliant with the following standards: Polish PNC 40007:2000, American ASTM D 330603 and British Standard BS 6580.  
Manufactured according to the PNEN ISO 9001:2008 quality management system.

PARAMETERS	UNIT	TYPICAL VALUES
colour		pink
density at 20°C	[g/ml]	1,065
boiling point	[°C]	109
pH		9

**NOTE:**  
Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each product lot.